Page 1 of 8

# MATERIAL SAFETY DATA SHEET

## **SECTION 1: IDENTIFICATION**

Product identifier : DIESEL FUEL CONDITIONER

Product Use : Diesel fuel additive .

Chemical Family : Mixture.

Manufacturer part no. : M7132C

Supplier's name and address: Manufacturer's name and address:

Radiator Specialty Co., of Canada Refer to Supplier

1711 Aimco Blvd.

Mississauga, ON, Canada

L4W 1H7

Information Telephone # : (905) 625-9117 (Mon. - Fri., 8 AM - 4 PM)

**24 Hr. Emergency Tel #** : 613-996-6666 (CANUTEC)

## SECTION 2 - HAZARDS IDENTIFICATION

#### Classification

: WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). WHMIS Classification:

Class B3 (Combustible Liquids);

Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material);

Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

Labelling: Phrases recommended to appear on a supplier label, can be found in Section 15. WHMIS symbols required on a supplier label:





#### **Emergency Overview**

Dark amber liquid. Petroleum odour.

Warning! Combustible liquid and vapour. Harmful if inhaled. Harmful or fatal if swallowed. May cause nausea, vomiting, headache and other central nervous system effects. May cause respiratory irritation. Could result in pulmonary edema (fluid accumulation). May be an aspiration hazard. Can enter the lungs and cause damage. Causes skin irritation. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Possible birth defect hazard - contains material that may cause birth defects, based on animal data. Possible cancer hazard - contains material which may cause cancer.

This product contains marine pollutants.

# **POTENTIAL HEALTH EFFECTS:**

## Signs and symptoms of short-term (acute) exposure

Inhalation: May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain,

headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Could result in pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath)

may be delayed.

Skin : May cause moderate skin irritation. May cause redness and itching or burning sensation. Product may be

absorbed.

Eyes: May cause mild eye irritation. Symptoms may include redness, itching and swelling.

Ingestion: May cause irritation of mouth, throat, and stomach. Ingestion may cause symptoms similar to inhalation.

Material is an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may

cause chemical pneumonitis, which can be fatal.

## Effects of long-term (chronic) exposure

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Repeated overexposure to naphthalene may cause destruction of red blood cells with

anemia, fever, jaundice and kidney and liver damage.

Carcinogenic status : Possible cancer hazard. See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : May cause birth defects. See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: This product contains marine pollutants. See ECOLOGICAL INFORMATION. Section 12.

Page 2 of 8

## SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	CAS#	Wt.%
,3,5-Trimethylbenzene	108-67-8	3.00 - 7.00
Kylene	1330-20-7	1.00 - 5.00
rimethylbenzene	25551-13-7	0.10 - 0.50
Petroleum naphtha	64742-94-5	1.00 - 5.00
stoddard solvent	8052-41-3	60.00 - 100.00
Naphthalene	91-20-3	0.10 - 0.50
1,2,4-Trimethylbenzene	95-63-6	1.00 - 5.00

## SECTION 4 - FIRST AID MEASURES

**Inhalation** : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.

**Skin contact** : Remove/Take off immediately all contaminated clothing. Wash exposed area thoroughly

with soap and water for at least 15 minutes. Get medical attention.

**Eye contact**: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists,

seek prompt medical attention.

**Ingestion**: Seek immediate medical attention/advice. Do not induce vomiting. Never give anything by

mouth to an unconscious person.

Notes For Physician : Treat symptomatically. This product is a CNS depressant.

## SECTION 5 - FIRE FIGHTING MEASURES

# Fire hazards/conditions of flammability

: Combustible liquid and vapour. Will ignite when exposed to heat, flame and other sources of ignition. Vapours may be heavier than air and may collect in confined and low-lying areas. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Product may float, and be re-ignited at the water's surface.

**Oxidizing properties** 

: None known.

Explosion data: Sensitivity to mechanical impact / static discharge

: May be sensitive to static discharge. Not expected to be sensitive to mechanical impact.

Suitable extinguishing media :

Dry chemical, foam, carbon dioxide and water fog. Do not use water jet, as this may spread burning material.

## Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

## **Hazardous combustion products**

 Carbon oxides; Nitrogen oxides (NOx); sulfur oxides; Aldehydes; Hydrocarbons; Other unidentified organic compounds.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

# Personal precautions

: All persons dealing with the clean-up should wear the appropriate personal protective equipment. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

# Environmental precautions Spill response/cleanup

: Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

: Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.

# Prohibited materials

: Do not use combustible materials, such as sawdust, as absorbent material.

Page 3 of 8

# **SECTION 7 - HANDLING AND STORAGE**

Safe Handling procedures

Use in a well-ventilated area. Wear suitable protective equipment during handling. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Avoid contact with incompatible materials. Wash thoroughly after handling. Launder clothing before reuse.

Storage requirements

Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials

: Strong oxidizing agents; Acids.

Special packaging materials

: Always keep in containers made of the same materials as the supply container.

# SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

	ACGIH	I TLV	OSHA PEL		
<u>Ingredients</u>	TWA	STEL	PEL	<u>STEL</u>	
1,3,5-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av	
Xylene	100 ppm	150 ppm	100 ppm ; 435 mg/m³	N/Av	
trimethylbenzene	25 ppm	N/Av	25 ppm (final rule limit)	N/Av	
Petroleum naphtha	N/Av	N/Av	500 ppm (as petroleum distillates, naphtha)	N/Av	
stoddard solvent	100 ppm	N/Av	500 ppm	N/Av	
Naphthalene	10 ppm (skin)	15 ppm (skin)	10 ppm	N/Av	
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av	

#### Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection

: Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers. Depending on conditions of use, an impervious apron should be worn.

Eye / face protection

: Safety glasses with side-shields or chemical splash goggles.

Other protective equipment

An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

# SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid.Appearance: red; ClearOdour: Petroleum odour.Odour threshold: N/Av

pH : N/Av

Boiling point: > 149°CSpecific gravity: 0.86Melting/Freezing point: N/AvCoefficient of water/oil distribution: N/Av

Vapour pressure (mmHg @ 20° C / 68° F) Solubility in water : slightly soluble

: N/Av

Vapour density (Air = 1) : N/Av Evaporation rate (n-Butyl acetate = 1)

: N/Av

Page 4 of 8

Volatile organic Compounds (VOC's) Volatiles (% by weight) : N/Av

: N/Av

: 60°C Flash point

Flash point Method Auto-ignition temperature Tag closed cup : N/Av Upper flammable limit (% by vol.) Lower flammable limit (% by vol.) : N/Av

: N/Av

Flame Projection Length Flashback observed : N/Ap : N/Ap Absolute pressure of container Viscosity : N/Av

: N/Ap

General Information : No additional information.

## **Section 10: STABILITY AND REACTIVITY**

: Stable under the recommended storage and handling conditions prescribed. Stability and reactivity

Hazardous polymerization : Hazardous polymerization does not occur.

Conditions to avoid Avoid heat and open flame. Keep away from direct sunlight. Ensure adequate ventilation,

especially in confined areas.

Materials To Avoid And Incompatibility

Strong oxidizing agents; Acids.

Hazardous decomposition products

Refer to Section 5 for additional 'Hazardous combustion products'.

# **SECTION 11 - TOXICOLOGICAL INFORMATION**

**Target organs** Eyes, skin, respiratory system, central nervous system, blood system, liver, brain and

kidneys.

Routes of exposure : Inhalation: YES Skin Absorption: YES Skin & Eyes: YES Ingestion: YES

Irritancy Moderate skin irritant. Mild eye irritant.

Toxicological data : There is no available data for the product itself, only for the ingredients. See below

for individual ingredient acute toxicity data.

	LC <sub>50</sub> (4hr)	LD <sub>50</sub>		
<u>Ingredients</u>	inh, rat	(Oral, rat)	(Rabbit, dermal)	
1,3,5-Trimethylbenzene	24 mg/L	23 000 mg/kg	N/Av	
Xylene	6350 ppm	3523 mg/kg	12 180 mg/kg	
trimethylbenzene	18 - 24 mg/L	8970 mg/kg	N/Av	
Petroleum naphtha	> 11.4 mg/L/6H	> 6000 mg/kg	> 3160 mg/kg	
stoddard solvent	> 5.5 mg/L	> 5000 mg/kg	> 3000 mg/kg	
Naphthalene	N/Av	2200 mg/kg (rat) 533 mg/kg (mouse)	20 000 mg/kg	
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg	

Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B) and Carcinogenic status

NTP (Group 2 - Reasonably anticipated).

Reproductive effects : Not expected to have other reproductive effects.

This product contains Xylene. Xylene may cause fetotoxic effects at doses which are not Teratogenicity

maternally toxic, based on animal data.

Mutagenicity Not expected to be mutagenic in humans.

No information available. **Epidemiology** 

Sensitization to material Not expected to be a skin or respiratory sensitizer.

Synergistic materials N/Av

other important hazards This product is a CNS depressant. CNS depression may result from extreme exposures.

# Conditions aggravated by overexposure

: Pre-existing eye, skin, respiratory, liver, kidney and central nervous system disorders. Blood disorders.

# **SECTION 12 - ECOLOGICAL INFORMATION**

## **Ecotoxicity**

: This product contains marine pollutants. No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. The product contains the following substances which are hazardous for the environment: stoddard solvent; Petroleum naphtha; 1,3,5-Trimethylbenzene; Xylene; 1,2,4-Trimethylbenzene; Trimethylbenzene; Naphthalene.

See the following tables for individual ingredient ecotoxicity data.

# Ecotoxicity data:

<u>Ingredients</u>		Toxicity to Fish		
	CAS No	LC50 / 96h	NOEC / 21 day	M Factor
1,3,5-Trimethylbenzene	108-67-8	12.52 mg/L (Goldfish)	N/Av	None.
Xylene	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
trimethylbenzene	25551-13-7	7.72 mg/L (Fathead minnow)	N/Av	None.
Petroleum naphtha	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	None.
stoddard solvent	8052-41-3	2.1 - 4.2 mg/L (Bluegill sunfish)	N/Av	None.
Naphthalene	91-20-3	0.11 mg/L (Rainbow trout)	0.12 mg/L	1
1,2,4-Trimethylbenzene	95-63-6	7.19 - 8.28 mg/L (Fathead minnow)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
1,3,5-Trimethylbenzene	108-67-8	50 mg/L/24hr (Daphnia magna)	N/Av	None.
Xylene	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
trimethylbenzene	25551-13-7	N/Av	N/Av	None.
Petroleum naphtha	64742-94-5	1.1 mg/L (Daphnia magna)	N/Av	None.
stoddard solvent	8052-41-3	N/Av	N/Av	None.
Naphthalene	91-20-3	2.16 mg/L (Daphnia magna)	0.22 mg/L	None.
1,2,4-Trimethylbenzene	95-63-6	6.14 mg/L (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
1,3,5-Trimethylbenzene	108-67-8	25 mg/L/48hr (Green algae)	N/Av	None.
Xylene	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
trimethylbenzene	25551-13-7	N/Av	N/Av	None.
Petroleum naphtha	64742-94-5	7.2 mg/L/72hr (Green algae)	0.22 mg/L/72hr	None.
stoddard solvent	8052-41-3	N/Av	N/Av	None.
Naphthalene	91-20-3	0.4 mg/L/72hr (Green algae)	N/Av	1
1,2,4-Trimethylbenzene	95-63-6	N/Av	N/Av	None.

#### Mobility

: No data is available on the product itself.

## Persistence

: No data is available on the product itself. Contains: stoddard solvent; Petroleum naphtha; 1,3,5-Trimethylbenzene; Xylene; 1,2,4-Trimethylbenzene; Trimethylbenzene; Naphthalene. Stoddard solvent is not considered to be readily biodegradable.

Petroleum naphtha is not considered readily biodegradable.

1,3,5-Trimethylbenzene is not expected to be readily biodegradable.

Xylene is considered to be inherently biodegradable.

1,2,4-Trimethylbenzene is not considered readily biodegradable. Trimethylbenzene is not considered to be readily biodegradable. Naphthalene is not considered to be readily biodegradable.

## **Bioaccumulation potential**

No data is available on the product itself. Contains: stoddard solvent;

1,3,5-Trimethylbenzene; Xylene; 1,2,4-Trimethylbenzene; Trimethylbenzene; Naphthalene. The log Kow value for stoddard solvent is 3.5 - 6.4.

1,3,5-Trimethylbenzene has a Bioconcentration Factor (BCF) of 23 - 328, and its log Pow value is 3.6 - 3.93.

The log Pow for Xvlene is 3.12.

The log Pow value for 1,2,4-Trimethylbenzene is 3.63, and its Bioconcentration Factor (BCF) is 31 - 275.

Trimethylbenzene has a Bioconcentration Factor (BCF) of 42 - 328, and its log Kow value is 3.63 (HSDB).

The log Kow value for Naphthalene is 3 - 3.5, and its bioconcentration factor (BCF) is 430.

## Other Adverse Environmental effects

: No data is available on the product itself.

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

**Handling for Disposal** 

: Handle waste according to recommendations in Section 7. Do not cut, weld, drill or grind on or near this container. Empty containers retain residue (liquid and/or vapour) and can be dangerous.

**Methods of Disposal** 

Dispose of in accordance with federal, provincial and local hazardous waste laws.

## SECTION 14: TRANPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1268	PETROLEUM PRODUCTS, N.O.S.	3	III	3
TDG Additional information	Regulations is a	r road or rail shipment if packaged in non-bulk containers (450 n exemption permitting the transportation of this product in smuct contains marine pollutants. This product contains: stoddard	all means of con	itainment as	not regulated.

Page 7 of 8

## **SECTION 15 - REGULATORY INFORMATION**

## Labelling:

Warning! Combustible liquid and vapour. Harmful if inhaled. Harmful or fatal if swallowed. May cause nausea, vomiting, headache and other central nervous system effects. May cause respiratory irritation. Could result in pulmonary edema (fluid accumulation). May be an aspiration hazard. Can enter the lungs and cause damage. Causes skin irritation. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Possible birth defect hazard - contains material that may cause birth defects, based on animal data. Contains material which may cause cancer, based on animal data.

Precautions: Use in a well-ventilated area. Wear suitable protective equipment during handling. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Avoid contact with incompatible materials. Wash thoroughly after handling. Store in a cool, dry, well ventilated area, away from heat and ignition sources.

FIRST AID: If inhaled, move to fresh air. If breathing stopped, begin artificial respiration. Get medical attention. For skin contact, wash with soap and water while removing contaminated clothing. Get medical attention. For eye contact, flush with running water for at least 15 minutes. If irritation persists, seek prompt medical attention. If ingested, do not induce vomiting. Immediately call a POISON CENTRE or doctor/physician. Never give anything by mouth to an unconscious person.

Refer To Material Safety Data Sheet for further information.

## **Canadian Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

#### **US Federal Information:**

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

## **SECTION 16 - OTHER INFORMATION**

Legend

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services CNS: Central Nervous System

HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

Inh: Inhalation

IUCLID: International Uniform Chemical Information Database

LC: Lethal Concentration

LD: Lethal Dose

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration

NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RTECS: Registry of Toxic Effects of Chemical Substances

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

Page 8 of 8

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2012.
  - 2. International Agency for Research on Cancer Monographs, searched 2013.
  - 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2013 (Chempendium, HSDB and RTECs).
  - Material Safety Data Sheets from manufacturer.
  - 5. OECD The Global Portal to Information on Chemical Substances eChemPortal, 2013.

# Prepared for:

Radiator Specialty Co. of Canada

1711 Aimco Blvd.

Mississauga, ON, Canada, L4W 1H7

Telephone: 905-625-9117 (Mon. - Fri., 8 AM - 4 PM) Please direct all enquiries to Radiator Specialty.

# Prepared by:

ICC The Compliance Center Inc.

http://www.thecompliancecenter.com



## DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

MSDS Preparation Date (mm/dd/yyyy)

: 08/07/2007

MSDS Revision Date (mm/dd/yyyy)

: 07/19/2013

Revision No. : 3

Revision Information : (M)SDS sections updated:

12. ECOLOGICAL INFORMATION.

END OF DOCUMENT