

Transp.  
Auto Shop



**Material Safety Data Sheet**  
May be used to comply with  
OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

**U.S. Department of Labor**  
Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

**IDENTITY (As Used on Label and List)**  
Wagner Premium Brake Fluid (H-104)

*Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

**Section I**

|   |  |
|---|--|
| Manufacturer's Name<br>Wagner Division-Cooper Industries, Inc.                                    | Emergency Telephone Number<br>1-800-424-9300                                       |
| Address (Number, Street, City, State, and ZIP Code)<br>100 Misty Lane<br><br>Parsippany, NJ 07054 | Telephone Number for Information<br>(201) 386-9300<br><br>Date Prepared<br>8/15/86 |
| Signature of Preparer (optional)<br><i>Joseph J. Fater, CIH</i> NATLSCO, Long Grove, IL           |  |

**Section II -- Hazardous Ingredients/Identity Information**

| Hazardous Components (Specific Chemical Identity; Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (optional) |
|---|----------|-----------|--------------------------|--------------|
|---|----------|-----------|--------------------------|--------------|

This product is a proprietary blend, consisting mainly of glycol ether.

Recent toxicological studies have shown reproductive effects in laboratory animals. All routes of exposure should be minimized.

**Section III -- Physical/Chemical Characteristics**

|                         |                  |   |                |
|-------------------------|------------------|---|----------------|
| Boiling Point<br>SAE    | 401°F<br>minimum | Specific Gravity (H <sub>2</sub> O = 1) | 1.0537         |
| Vapor Pressure (mm Hg.) | not determined   | Melting Point                           | not determined |
| Vapor Density (AIR = 1) | not determined   | Evaporation Rate<br>(Butyl Acetate = 1) | not determined |

Solubility in Water  
soluble

Appearance and Odor  
Clear to amber with ether-like odors.

**Section IV -- Fire and Explosion Hazard Data**

|  |                                    |           |           |
|--|------------------------------------|-----------|-----------|
| Flash Point (Method Used)<br>COC 250°F | Flammable Limits<br>not determined | LEL<br>-- | UEL<br>-- |
|--|------------------------------------|-----------|-----------|

Extinguishing Media  
Water, Dry Chemical, Alcohol Foam, Carbon Dioxide

Special Fire Fighting Procedures  
Use NIOSH/MSHA approved positive-pressure self-contained breathing apparatus where this material is involved in a fire.

Unusual Fire and Explosion Hazards  
None.

