

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 3/3/08

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

(847) 541-5700
(800) 424-9300

FOR INFORMATION:

(847) 541-5700

- SUNNYSIDE CORPORATION
- CHEM TREC

Product Class: Solvent/Surfactant/water Mixture
Trade Name: Green Envy Paint Thinner

Manufacturer's Code:
NPCA HMIS:

730
Health: 1
Flammability: 2
Reactivity: 1

Product Appearance and Odor: Milky emulsion; sweet, naphthalenic odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Parachlorobenzo-trifluoride	98-56-6	<5%	Not est.	Not est.	Not est.	Not est.	5.3 MM Hg @ 20° C.
Dipropylene Glycol Methyl ether	34590-94-8	<5%	100PPM (Skin)	150 PPM (Skin)	100PPM	150PPM	0.4 MM Hg @ 77deg. C
Petroleum Distillate	64741-65-7	<5%	Not Established	Not Established	500 PPM	500PPM	Not Available
Sodium dioctyl Sulfosuccinate	577-11-7	<5%	Not Established	Not Est.	Not Est.	Not Est.	Not Available

Components not listed are not hazardous or are below reportable limits.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

Inhalation: If overcome by vapors, remove to fresh air and get medical attention.

Eyes: In case of eye contact, flush thoroughly with water and get medical attention.

Skin: In case of skin contact, wash thoroughly with mild soap and water and get medical attention if irritation persists.

Ingestion: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	212° F. (I.B.P.)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	8% (Approx.)
Weight Per Gallon:	8.46 Lbs.	VOC: 19g/L.	
Solubility in Water:	Complete		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification(NFPA):	Combustible Liquid - Class II.
Flash Point:	111° F. Tag Closed Cup
Autoignition Temperature:	Not Available
Lower Explosive Limit:	Not Available
Extinguishing Media:	Water spray, dry chemical, CO2, alcohol foam.
Unusual Fire and Explosion Hazards:	Do not store or mix with strong oxidants.
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Use water spray to keep fire-exposed containers cool.

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: EFFECTS OF OVEREXPOSURE	OSHA and ACGIH exposure limits have not been established. See Section 2.
Inhalation:	May cause headache, dizziness, nausea, loss of balance and drowsiness
Skin:	May be irritating.
Eyes:	May be irritating.
Ingestion:	May damage lining of gastro-intestinal tract.

SECTION 7 -- REACTIVITY DATA

Stability:	Stable.
Conditions to Avoid:	Heat, sparks, flame.
Incompatibility (Materials to Avoid):	Oxidizing materials can cause a reaction.
Hazardous Decomposition Products:	Chlorine and Fluorine containing gases can be produced.
Hazardous Polymerization:	Will not occur.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapor or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection:	An appropriate NIOSH-approved respirator for organic vapor should be worn if needed.
Ventilation:	Local exhaust should be used to control vapors. Maintain workroom air concentrations below irritating levels.
Protective Gloves:	Solvent resistant.
Eye Protection:	Wear chemical safety goggles plus full face shield when appropriate.
Other Protective Equipment:	Good industrial hygiene practice should be followed, which includes preventing eye contact, minimizing skin contact and minimizing inhalation of vapors. An eye wash and washing facilities should be available.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category:	Combustible Liquid - Class II.
Hygienic Practices:	Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact. Store away from heat and light.
Additional Precautions:	Ground containers when transferring liquid to prevent static accumulation and discharge. Additional information regarding safe handling of products with static accumulation potential can be ordered by contacting the American Petroleum Institute (API) for API Recommended Practice 2003, entitled "Protection Against Ignitions Arising Out of Static, Lighting, and Stray Currents" (American Petroleum Institute, 1720 L Street Northwest, Washington, DC 20005), or the National Fire Protection Association (NFPA) for NFPA 77 entitled "Static Electricity" (National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101).
Empty Container Warning:	"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 11 -- ADDITIONAL INFORMATION

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
NONE	NONE	NONE

SARA Title III Hazard Categories: Delayed (chronic) health hazard, fire hazard

TRANSPORTATION

(U. S. LAND TRANSPORTATION IN PACKAGES OF 119 GALS OR LESS) NOT REGULATED BY U. S. D.O.T. AS A HAZARDOUS MATERIAL.